

SAFETY DATA SHEET**SECTION 1: Identification of the substance/mixture and of the company/undertaking****1.1 Product identifier**

Product name	Aral Heizöl / Aral HeizölPlus
UFI:	675-80KW-U00X-D6T4
Other means of identification	Heating oil in accordance with standard DIN 51603-1.
Proper shipping name	MARPOL Annex 1 rules apply for bulk shipments by sea. Category: gas oils, including ship's bunkers
SDS #	SGY2152
Product type	Liquid.

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture	Fuel for industrial or domestic boilers; fuel for compression ignition diesel engines. For specific application advice see appropriate Technical Data Sheet or consult our company representative.
-------------------------------------	---

1.3 Details of the supplier of the safety data sheet

Supplier	Aral Aktiengesellschaft Wittener Str. 45 44789 Bochum Germany Telefon: +49 (0) 234 315-0
E-mail address	MSDSadvice@bp.com


1.4 Emergency telephone number

EMERGENCY TELEPHONE NUMBER	+49 (0) 30 30686 790 (Giftnotruf Berlin/Emergency Poison Centre)
-----------------------------------	--

SECTION 2: Hazards identification**2.1 Classification of the substance or mixture**

Product definition	Mixture
---------------------------	---------

Classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

 am. Liq. 3, H226
 Acute Tox. 4, H332
 Skin Irrit. 2, H315
 Carc. 2, H351
 Repr. 1B, H360FD
 STOT RE 2, H373 (bone marrow, liver, thymus)
 Asp. Tox. 1, H304
 Aquatic Chronic 2, H411

See Section 16 for the full text of the H statements declared above.

See sections 11 and 12 for more detailed information on health effects and symptoms and environmental hazards.

2.2 Label elements



UFI:	675-80KW-U00X-D6T4
-------------	--------------------

Hazard pictograms


Signal word	Danger
--------------------	--------

Product name	Aral Heizöl / Aral HeizölPlus	Product code	SGY2152	Page:	1/19
Version	12	Date of issue	26 March 2026	Format	Germany
Date of previous issue	9 January 2024.			Language	ENGLISH
					(Germany)

SECTION 2: Hazards identification

Hazard statements	<p> H226 - Flammable liquid and vapour. H304 - May be fatal if swallowed and enters airways. H315 - Causes skin irritation. H332 - Harmful if inhaled. H351 - Suspected of causing cancer. H360FD - May damage fertility. May damage the unborn child. H373 - May cause damage to organs through prolonged or repeated exposure. (bone marrow, liver, thymus) H411 - Toxic to aquatic life with long lasting effects.</p>
<u>Precautionary statements</u>	
General	P102 - Keep out of reach of children.
Prevention	<p>P201 - Obtain special instructions before use. P280 - Wear protective gloves, protective clothing, eye protection, face protection, or hearing protection. P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P271 - Use only outdoors or in a well-ventilated area. P273 - Avoid release to the environment. P260 - Do not breathe vapour or spray. P264 - Wash hands thoroughly after handling.</p>
Response	<p>P391 - Collect spillage. P308 + P313 - IF exposed or concerned: Get medical attention. P304 + P312 - IF INHALED: Call a POISON CENTER or doctor if you feel unwell. P301 + P310, P331 - IF SWALLOWED: Immediately call a POISON CENTER or physician. Do NOT induce vomiting. P362 + P364 - Take off contaminated clothing and wash it before reuse.</p>
Storage	P405 - Store locked up.
Disposal	P501 - Dispose of contents and container in accordance with all local, regional, national and international regulations.
Hazardous ingredients	 uels, diesel
Supplemental label elements	Not applicable.

EU Regulation (EC) No. 1907/2006 (REACH)


Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles  Restricted to professional users.

Special packaging requirements

Containers to be fitted with child-resistant fastenings Yes, applicable.
Tactile warning of danger Yes, applicable.

2.3 Other hazards

Product meets the criteria for PBT or vPvB according to Regulation (EC) No. 1907/2006, Annex XIII This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

Product meets the criteria for endocrine disrupting properties according to Regulation (EC) No. 1907/2006.  This substance/mixture does not contain any components that are considered to have endocrine disrupting properties.

Other hazards which do not result in classification Static accumulating flammable liquid can become electrostatically charged even in bonded and grounded equipment. Sparks may ignite liquid and vapour may cause flash fire or explosion.
 This material may contain significant quantities of polycyclic aromatic hydrocarbons, some of which have been shown by experimental studies to induce skin cancer.
 Note: High Pressure Applications
 Injections through the skin resulting from contact with the product at high pressure constitute a major medical emergency.
 See 'Notes to physician' under First-Aid Measures, Section 4 of this Safety Data Sheet.

Product name Aral Heizöl / Aral HeizölPlus	Product code SGY2152	Page: 2/19
Version 12	Date of issue 26 March 2026	Format Germany
Date of previous issue 9 January 2024.		Language ENGLISH
	(Germany)	

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Product definition Mixture

Complex mixture of middle distillate hydrocarbons, with carbon numbers in C10 to C28 range. May also contain small quantities of proprietary performance additives.

Product/ingredient name	Identifiers	%	Classification	Specific Conc. Limits, M-factors and ATEs	Type
Fuels, diesel	REACH #: 01-2119484664-27 EC: 269-822-7 CAS: 68334-30-5 Index: 649-224-00-6	≥90	Flam. Liq. 3, H226 Acute Tox. 4, H332 Skin Irrit. 2, H315 Carc. 2, H351 Repr. 1B, H360FD STOT RE 2, H373 (bone marrow, liver, thymus) Asp. Tox. 1, H304 Aquatic Chronic 2, H411	ATE [Inhalation (dusts and mists)] = 4.1 mg/l	[1]

See Section 16 for the full text of the H statements declared above.

Type

[1] Substance classified with a health or environmental hazard

Occupational exposure limits, if available, are listed in Section 8.

SECTION 4: First aid measures

4.1 Description of first aid measures

Eye contact	In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. Eyelids should be held away from the eyeball to ensure thorough rinsing. Check for and remove any contact lenses. Get medical attention.
Skin contact	In case of contact, immediately flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes. Drench contaminated clothing with water before removing. This is necessary to avoid the risk of sparks from static electricity that could ignite contaminated clothing. Contaminated clothing is a fire hazard. Contaminated leather, particularly footwear, must be discarded. Wash clothing before reuse. Clean shoes thoroughly before reuse. Get medical attention.
Inhalation	If inhaled, remove to fresh air. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. Get medical attention immediately.
Ingestion	Do not induce vomiting. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Aspiration hazard if swallowed. Can enter lungs and cause damage. Get medical attention immediately.
Protection of first-aiders	No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation.

4.2 Most important symptoms and effects, both acute and delayed

See Section 11 for more detailed information on health effects and symptoms.

Potential acute health effects

Inhalation	Harmful if inhaled.
Ingestion	Irritating to mouth, throat and stomach. Aspiration hazard if swallowed -- harmful or fatal if liquid is aspirated into lungs.
Skin contact	Causes skin irritation.
Eye contact	See: Section 11. Toxicological information - Potential acute health effects: Eye contact

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Inhalation	Vapour, mists or fumes may contain polycyclic aromatic hydrocarbons some of which are known to produce skin cancer. May be harmful by inhalation if exposure to vapour, mists or fumes resulting from thermal decomposition products occurs. Vapour, mist or fume may irritate the nose, mouth and respiratory tract.
Ingestion	If swallowed, may irritate the mouth, throat and digestive system. If swallowed, may cause abdominal pain, stomach cramps, nausea, vomiting, diarrhoea, dizziness and drowsiness.
Skin contact	As with all such products containing potentially harmful levels of polycyclic aromatic hydrocarbons, prolonged or repeated skin contact may eventually result in dermatitis or more serious irreversible skin disorders including cancer.
Eye contact	Vapour, mist or fume may cause eye irritation. Exposure to vapour, mist or fume may cause stinging, redness and watering of the eyes.

Product name Aral Heizöl / Aral HeizölPlus	Product code SGY2152	Page: 3/19
Version 12	Date of issue 26 March 2026	Format Germany
Date of previous issue 9 January 2024.		Language ENGLISH
	(Germany)	

SECTION 4: First aid measures

4.3 Indication of any immediate medical attention and special treatment needed

Notes to physician

Treatment should in general be symptomatic and directed to relieving any effects. Product can be aspirated on swallowing or following regurgitation of stomach contents, and can cause severe and potentially fatal chemical pneumonitis, which will require urgent treatment. Because of the risk of aspiration, induction of vomiting and gastric lavage should be avoided. Gastric lavage should be undertaken only after endotracheal intubation. Monitor for cardiac dysrhythmias.

Note: High Pressure Applications
 Injections through the skin resulting from contact with the product at high pressure constitute a major medical emergency. Injuries may not appear serious at first but within a few hours tissue becomes swollen, discoloured and extremely painful with extensive subcutaneous necrosis. Surgical exploration should be undertaken without delay. Thorough and extensive debridement of the wound and underlying tissue is necessary to minimise tissue loss and prevent or limit permanent damage. Note that high pressure may force the product considerable distances along tissue planes.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media

In case of fire, use water fog, foam, dry chemical or carbon dioxide extinguisher or spray.

Unsuitable extinguishing media

Do not use water jet. The use of a water jet may cause the fire to spread by splashing the burning product.

5.2 Special hazards arising from the substance or mixture

Hazards from the substance or mixture

Flammable liquid and vapour. In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion. Runoff to sewer may create fire or explosion hazard. Vapours can form explosive mixtures with air. Vapours are heavier than air and can spread along the ground or float on water surfaces to remote ignition sources. Vapours may accumulate in low or confined areas or travel a considerable distance to a source of ignition and flash back. Liquid will float and may reignite on surface of water.

Hazardous combustion products

Combustion products may include the following:
 carbon oxides (CO, CO₂) (carbon monoxide, carbon dioxide)

5.3 Advice for firefighters

Special precautions for fire-fighters

No action shall be taken involving any personal risk or without suitable training. Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool. This material is toxic to aquatic organisms. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.

Special protective equipment for fire-fighters

Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. Clothing for fire-fighters (including helmets, protective boots and gloves) conforming to European standard EN 469 will provide a basic level of protection for chemical incidents.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

Immediately contact emergency personnel. No action shall be taken involving any personal risk or without suitable training. Eliminate all ignition sources. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Floors may be slippery; use care to avoid falling. No flares, smoking or flames in hazard area. Avoid breathing vapour or mist. Provide adequate ventilation. Put on appropriate personal protective equipment.

For emergency responders

Entry into a confined space or poorly ventilated area contaminated with vapour, mist or fume is extremely hazardous without the correct respiratory protective equipment and a safe system of work. Wear self-contained breathing apparatus. Wear a suitable chemical protective suit. Chemical resistant boots. See also the information in "For non-emergency personnel".

SECTION 6: Accidental release measures

6.2 Environmental precautions

Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities. Collect spillage. In case of small spillages in closed waters (i.e. ports), contain product with floating barriers or other equipment. Collect spilled product by absorbing with specific floating absorbents. If possible, large spillages in open waters should be contained with floating barriers or other mechanical means. If this is not possible, control the spreading of the spillage, and collect the product by skimming or other suitable mechanical means. The use of dispersants should be advised by an expert, and, if required, approved by local authorities. Collect recovered product and other contaminated materials in suitable tanks or containers for recycle, recovery or safe disposal.

6.3 Methods and material for containment and cleaning up

Small spill

Eliminate all ignition sources. Stop leak if without risk. Move containers from spill area. Absorb with an inert material and place in an appropriate waste disposal container. Use spark-proof tools and explosion-proof equipment. Dispose of via a licensed waste disposal contractor. The method and equipment used must be in conformance with appropriate regulations and industry practice on explosive atmospheres.

Large spill

Eliminate all ignition sources. Stop leak if without risk. Move containers from spill area. Approach the release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Dike spill area and do not allow product to reach sewage system and surface or ground water. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations. Use spark-proof tools and explosion-proof equipment. Contaminated absorbent material may pose the same hazard as the spilt product. The method and equipment used must be in conformance with appropriate regulations and industry practice on explosive atmospheres. Dispose of via a licensed waste disposal contractor.

6.4 Reference to other sections

See Section 1 for emergency contact information.
 See Section 5 for firefighting measures.
 See Section 8 for information on appropriate personal protective equipment.
 See Section 12 for environmental precautions.
 See Section 13 for additional waste treatment information.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Protective measures

Put on appropriate personal protective equipment. Avoid exposure - obtain special instructions before use. Avoid exposure during pregnancy. Do not handle until all safety precautions have been read and understood. Do not get in eyes or on skin or clothing. Do not breathe vapour or mist. Do not swallow. Aspiration hazard if swallowed. Can enter lungs and cause damage. Never siphon by mouth. Avoid contact of spilt material and runoff with soil and surface waterways. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Store and use away from heat, sparks, open flame or any other ignition source. Use explosion-proof electrical (ventilating, lighting and material handling) equipment. Use only non-sparking tools. Take precautionary measures against electrostatic discharges. Do not reuse container. Empty containers retain product residue and can be hazardous.

Advice on general occupational hygiene

Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Wash thoroughly after handling. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

7.2 Conditions for safe storage, including any incompatibilities

Store in accordance with local regulations. Store in a segregated and approved area. Store in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10). Store locked up. Keep away from heat and direct sunlight. Eliminate all ignition sources. Separate from oxidising materials. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Store and use only in equipment/containers designed for use with this product. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination.

Light hydrocarbon vapours can build up in the headspace of tanks. These can cause flammability/explosion hazards even at temperatures below the normal flash point (note: flash point must not be regarded as a reliable indicator of the potential flammability of vapour in tank headspaces). Tank headspaces should always be regarded as potentially flammable and care should be taken to avoid static electrical discharge and all ignition sources during filling, ullaging and sampling from storage tanks. Do not enter storage tanks. If entry to vessels is

Product name Aral Heizöl / Aral HeizölPlus

Product code SGY2152

Page: 5/19

Version 12 **Date of issue** 26 March 2026

Format Germany

Language ENGLISH

Date of previous issue 9 January 2024.

(Germany)

SECTION 7: Handling and storage

necessary, follow permit to work procedures. Entry into a confined space or poorly ventilated area contaminated with vapour, mist or fume is extremely hazardous without the correct respiratory protective equipment and a safe system of work. When the product is pumped (e.g. during filling, discharge or ullaging) and when sampling, there is a risk of static discharge. Ensure equipment used is properly earthed or bonded to the tank structure. Electrical equipment should not be used unless it is intrinsically safe (i.e. will not produce sparks). Explosive air/vapour mixtures may form at ambient temperature. If product comes into contact with hot surfaces, or leaks occur from pressurised fuel pipes, the vapour or mists generated will create a flammability or explosion hazard. Product contaminated rags, paper or material used to absorb spillages, represent a fire hazard, and should not be allowed to accumulate. Dispose of safely immediately after use.

Germany - Storage code

3

7.3 Specific end use(s)

Recommendations

See section 1.2 and Exposure scenarios in annex, if applicable.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational exposure limits

No exposure limit value known.

Whilst specific OELs for certain components may be shown in this section, other components may be present in any mist, vapour or dust produced. Therefore, the specific OELs may not be applicable to the product as a whole and are provided for guidance only.

Recommended monitoring procedures

Reference should be made to monitoring standards, such as the following: European Standard EN 689 (Workplace atmospheres - Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) European Standard EN 14042 (Workplace atmospheres - Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) European Standard EN 482 (Workplace atmospheres - General requirements for the performance of procedures for the measurement of chemical agents) Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

Biological exposure indices

Product/ingredient name

Exposure indices

No exposure indices known.

DNELs/DMELs

Product/ingredient name

Fuels, diesel

Result

DNEL - Workers - Short term - Inhalation

4300 mg/m³

Effects: Systemic

15 minutes

DNEL - Workers - Long term - Dermal

2.9 mg/kg bw/day

Effects: Systemic

8 hours TWA

DNEL - Workers - Long term - Inhalation

68 mg/m³

Effects: Systemic

8 hours TWA

DNEL - General population - Consumers - Short term - Inhalation

2600 mg/m³

Effects: Systemic

15 minutes

DNEL - General population - Consumers - Long term - Dermal

1.3 mg/kg bw/day

Effects: Systemic

TWA

DNEL - General population - Consumers - Long term - Inhalation

20 mg/m³

Effects: Systemic

Product name Aral Heizöl / Aral HeizölPlus

Product code SGY2152

Page: 6/19

Version 12 Date of issue 26 March 2026

Format Germany

Language ENGLISH

Date of previous issue 9 January 2024.

(Germany)

SECTION 8: Exposure controls/personal protection

24 hours TWA

PNECs

Not available.

8.2 Exposure controls

Appropriate engineering controls

Provide exhaust ventilation or other engineering controls to keep the relevant airborne concentrations below their respective occupational exposure limits. All activities involving chemicals should be assessed for their risks to health, to ensure exposures are adequately controlled. Personal protective equipment should only be considered after other forms of control measures (e.g. engineering controls) have been suitably evaluated. Personal protective equipment should conform to appropriate standards, be suitable for use, be kept in good condition and properly maintained. Your supplier of personal protective equipment should be consulted for advice on selection and appropriate standards. For further information contact your national organisation for standards. The final choice of protective equipment will depend upon a risk assessment. It is important to ensure that all items of personal protective equipment are compatible.

Individual protection measures

Hygiene measures

Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Ensure that eyewash stations and safety showers are close to the workstation location.

Respiratory protection

If local exhaust ventilation or other methods of ventilation are not possible or are insufficient, wear suitable respiratory protective devices. Wear suitable respiratory protective devices if there is a risk of exposure limits being exceeded. The choice of suitable respiratory device will depend upon a risk assessment of the workplace environment and the task being carried out. If required, the respiratory device must be certified as safe in defined explosive atmospheres (EX Label). Respiratory protective devices must be checked to ensure they fit correctly each time they are worn. Please consult European standard EN 529 for further guidance on the selection, use, care and maintenance of respiratory protective devices.

Suitable breathing apparatus (independent of ambient atmosphere) must be worn if any of the following situations apply.

- When the workplace atmosphere is considered to be immediately dangerous to life and health.
- When there is a risk of the workplace atmosphere being oxygen deficient.
- When the workplace atmosphere is uncontrolled.
- When the workplace atmosphere is unknown.
- When there is a risk of loss of consciousness or asphyxiation
- When entry into a confined space is required.
- When there is a risk of gases being released that could be a fire or explosion hazard.
- When the concentration of contaminants in the atmosphere exceeds the level of protection (maximum allowed concentration) given by a filtering device
- When the contaminants have a low odour that would not be tasted or smelt by the wearer of a filtering device if the filter became exhausted or saturated.
- When there is a risk of hydrogen sulphide exposure limits being exceeded.

Use with adequate ventilation.

If there is a requirement for the use of a respiratory protective device, but the use of breathing apparatus (independent of ambient atmosphere) is not required, then a suitable filtering device must be worn.

The filter class must be suitable for the maximum contaminant concentration (gas/vapour/ aerosol/particulates) that may arise when handling the product.

Recommended: Gas filter suitable for gases and vapours. Filter type: A
 Combined filter suitable for gases, vapours and particles (dust, smoke, mist, aerosol). Filter type: AP

Eye/face protection

Chemical splash goggles.

Skin protection

Hand protection

General Information:

Because specific work environments and material handling practices vary, safety procedures should be developed for each intended application. The correct choice of protective gloves depends upon the chemicals being handled, and the conditions of work and use. Most gloves provide protection for only a limited time before they must be discarded and replaced (even the best chemically resistant gloves will break down after repeated chemical exposures).

Gloves should be chosen in consultation with the supplier / manufacturer and taking account of a full assessment of the working conditions.

Wear chemical resistant gloves.
 Recommended: Nitrile gloves.

Product name Aral Heizöl / Aral HeizölPlus	Product code SGY2152	Page: 7/19
Version 12	Date of issue 26 March 2026	Format Germany
Date of previous issue 9 January 2024.		Language ENGLISH
	(Germany)	

SECTION 8: Exposure controls/personal protection

Do not re-use gloves.

Protective gloves will deteriorate over time due to physical and chemical damage. Inspect and replace gloves on a regular basis.

Protective gloves must give suitable protection against mechanical risks (i.e. abrasion, blade cut and puncture).

The frequency of replacement will depend upon the circumstances of use.

Breakthrough time:

Breakthrough time data are generated by glove manufacturers under laboratory test conditions and represent how long a glove can be expected to provide effective permeation resistance. It is important when following breakthrough time recommendations that actual workplace conditions are taken into account. Always consult with your glove supplier for up-to-date technical information on breakthrough times for the recommended glove type.

Our recommendations on the selection of gloves are as follows:

Continuous contact:

Gloves with a minimum breakthrough time of 240 minutes, or >480 minutes if suitable gloves can be obtained.

If suitable gloves are not available to offer that level of protection, gloves with shorter breakthrough times may be acceptable as long as appropriate glove maintenance and replacement regimes are determined and adhered to.

Short-term / splash protection:

Recommended breakthrough times as above.

It is recognised that for short-term, transient exposures, gloves with shorter breakthrough times may commonly be used. Therefore, appropriate maintenance and replacement regimes must be determined and rigorously followed.

Glove Thickness:

For general applications, we recommend gloves with a thickness typically greater than 0.35 mm.

It should be emphasised that glove thickness is not necessarily a good predictor of glove resistance to a specific chemical, as the permeation efficiency of the glove will be dependent on the exact composition of the glove material. Therefore, glove selection should also be based on consideration of the task requirements and knowledge of breakthrough times.

Glove thickness may also vary depending on the glove manufacturer, the glove type and the glove model. Therefore, the manufacturers' technical data should always be taken into account to ensure selection of the most appropriate glove for the task.

Note: Depending on the activity being conducted, gloves of varying thickness may be required for specific tasks. For example:

- Thinner gloves (down to 0.1 mm or less) may be required where a high degree of manual dexterity is needed. However, these gloves are only likely to give short duration protection and would normally be just for single use applications, then disposed of.

- Thicker gloves (up to 3 mm or more) may be required where there is a mechanical (as well as a chemical) risk i.e. where there is abrasion or puncture potential.

Recommended: Nitrile gloves.

Wear suitable protective clothing.

Footwear highly resistant to chemicals.

When there is a risk of ignition wear inherently fire resistant protective clothes and gloves.

Refer to standard: ISO 11612

When there is a risk of ignition from static electricity, wear anti-static protective clothing. For greatest effectiveness against static electricity, overalls, boots and gloves should all be anti-static.

Refer to standard: EN 1149

Cotton or polyester/cotton overalls will only provide protection against light superficial contamination.

When the risk of skin exposure is high (from experience this could apply to the following tasks: cleaning work, maintenance and service, filling and transfer, taking samples and cleaning up spillages) then a chemical protective suit and boots will be required.

Work clothing / overalls should be laundered on a regular basis. Laundering of contaminated

Skin and body

Product name Aral Heizöl / Aral HeizölPlus

Product code SGY2152

Page: 8/19

Version 12 **Date of issue** 26 March 2026

Format Germany

Language ENGLISH

Date of previous issue 9 January 2024.

(Germany)

SECTION 8: Exposure controls/personal protection

work clothing should only be done by professional cleaners who have been told about the hazards of the contamination. Always keep contaminated work clothing away from uncontaminated work clothing and uncontaminated personal clothes.

Refer to standards:

Respiratory protection: EN 529
 Gloves: EN 420, EN 374
 Eye protection: EN 166
 Filtering half-mask: EN 149
 Filtering half-mask with valve: EN 405
 Half-mask: EN 140 plus filter
 Full-face mask: EN 136 plus filter
 Particulate filters: EN 143
 Gas/combined filters: EN 14387

Environmental exposure controls

Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

SECTION 9: Physical and chemical properties

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

9.1 Information on basic physical and chemical properties

Physical state	Liquid.
Colour	Red.
Odour	Gas oil
Odour threshold	0.7 ppm (Based on Fuels, diesel)
Melting point/freezing point	-29 to -18°C (-20.2 to -0.4°F) (Based on Fuels, diesel)
Initial boiling point and boiling range	170 to 390°C (338 to 734°F)
Flammability	Flammable liquid and vapour.
Lower and upper explosion limit	Lower: 0.6% Upper: 6.5% Based on Diesel fuel
Flash point	Closed cup: >55°C (>131°F)
Auto-ignition temperature	254 to 285°C (489.2 to 545°F) (Based on Fuels, diesel)
Decomposition temperature	Not observed to decompose by final boiling point: >390°C (>734°F)
pH	Not applicable. Based on Solubility in Water (Very slightly soluble in water)
Kinematic viscosity	Kinematic: <7 mm ² /s (<7 cSt) at 40°C Kinematic: 2.5 to 6 mm ² /s (2.5 to 6 cSt) at 20°C
Solubility	

Media	Result
water	Very slightly soluble

Partition coefficient n-octanol/water (log value) Not applicable. Based on Fuels, diesel - Substance is a hydrocarbon UVCB. Standard tests for this endpoint are intended for single substances and are not appropriate for this complex substance.

Vapour pressure 0.4 kPa (3 mm Hg) [40°C (104°F)] (Based on Concawe Category: Vacuum Gas Oils, Hydrocracked Gas Oils & Distillate Fuels (VHGO))

Density and/or Relative density 0.815 to 0.86

Density and/or Relative density 815 to 860 kg/m³ (0.815 to 0.86 g/cm³) at 15°C

Relative vapour density >1 [Air = 1]

Particle characteristics

Median particle size Not applicable.

9.2 Other information

Evaporation rate Not relevant/applicable due to nature of the product. Based on low volatility

Explosive properties Based on Fuels, diesel - Not considered explosive based on structural and oxygen balance considerations.

Flammable liquid and vapour. Vapours may form explosive mixtures with air.

Oxidising properties Based on Fuels, diesel - Not considered oxidizing based on structural considerations.

Miscible with water No.

SECTION 10: Stability and reactivity

- 10.1 Reactivity** No specific test data available for this product. Refer to Conditions to avoid and Incompatible materials for additional information.
- 10.2 Chemical stability** The product is stable.
- 10.3 Possibility of hazardous reactions** Under normal conditions of storage and use, hazardous reactions will not occur. Under normal conditions of storage and use, hazardous polymerisation will not occur.
- 10.4 Conditions to avoid** Avoid all possible sources of ignition (spark or flame). Avoid excessive heat.
- 10.5 Incompatible materials** Reactive or incompatible with the following materials: oxidising materials.
- 10.6 Hazardous decomposition products** Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Product/ingredient name

Fuels, diesel

Result

Rat - Oral - LD50

17900 mg/kg
Equivalent to OECD 401
Based on No. 2 Heating Oil.

Rat - Oral - LD50

7600 mg/kg
Equivalent to OECD 420
Based on Diesel fuel

Rabbit - Dermal - LD50

>4300 mg/kg
Equivalent to OECD 434
Based on No. 2 Heating Oil. / Diesel fuel

Rat - Inhalation - LC50 Dusts and mists

4.1 mg/l [4 hours]
Equivalent to OECD 403
Based on Diesel fuel

Conclusion/Summary [Product]

Harmful if inhaled.

Ingredient name

Fuels, diesel

Conclusion/Summary

Harmful if inhaled.

Acute toxicity estimates

Product/ingredient name	Oral (mg/kg)	Dermal (mg/kg)	Inhalation (gases) (ppm)	Inhalation (vapours) (mg/l)	Inhalation (dusts and mists) (mg/l)
Fuels, diesel	N/A	N/A	N/A	N/A	4.1
Aral Heizöl / Aral HeizölPlus	N/A	N/A	N/A	N/A	4.1

Skin corrosion/irritation

Product/ingredient name

Fuels, diesel

Result

Rabbit - Skin - Irritation

Equivalent to OECD 404
Based on Diesel fuel

Conclusion/Summary [Product]

Causes skin irritation.

Ingredient name

Fuels, diesel

Conclusion/Summary

Causes skin irritation.

Serious eye damage/eye irritation

Product name Aral Heizöl / Aral HeizölPlus	Product code SGY2152	Page: 10/19
Version 12	Date of issue 26 March 2026	Format Germany
Date of previous issue 9 January 2024.	(Germany)	Language ENGLISH

SECTION 11: Toxicological information

Product/ingredient name

Fuels, diesel

Result

Rabbit - Eyes - Non-irritating to the eyes.
Equivalent to OECD 405
Based on Diesel fuel

Conclusion/Summary [Product]

Not classified. Based on available data, the classification criteria are not met.

Ingredient name

Fuels, diesel

Conclusion/Summary

Not classified. Based on available data, the classification criteria are not met.

Respiratory corrosion/irritation

Not available.

Respiratory or skin sensitization

Product/ingredient name

Fuels, diesel

Result

Guinea pig - skin
Equivalent to OECD 406
Result: Not sensitising
Based on Diesel fuel

Skin

Conclusion/Summary [Product]

Not classified. Based on available data, the classification criteria are not met.

Ingredient name

Fuels, diesel

Conclusion/Summary

Not classified. Based on available data, the classification criteria are not met.

Germ cell mutagenicity

Product/ingredient name

Fuels, diesel

Result

In vitro - Non-mammalian species
OECD 471
Result: Positive
Based on Diesel fuel

In vitro - Mammalian-Animal - Germ

Equivalent to OECD 476
Result: Negative
Based on Heating Oil.

In vivo - Unspecified - Somatic

not guideline
Result: Negative
Based on Heating Oil.

Conclusion/Summary [Product]

Not classified. Based on available data, the classification criteria are not met.

Ingredient name

Fuels, diesel

Conclusion/Summary

Not classified. Based on available data, the classification criteria are not met.

Carcinogenicity

Product/ingredient name

Fuels, diesel

Result

Mouse - Dermal - Unspecified
Equivalent to OECD 451
2 years
Result: Positive
Based on Heating Oil.

Conclusion/Summary [Product]

Suspected of causing cancer.

Ingredient name

Fuels, diesel

Conclusion/Summary

Suspected of causing cancer.

Reproductive toxicity

Product name Aral Heizöl / Aral HeizölPlus

Product code SGY2152

Page: 11/19

Version 12 **Date of issue** 26 March 2026

Format Germany

Language ENGLISH

Date of previous issue 9 January 2024.

(Germany)

SECTION 11: Toxicological information

Product/ingredient name

Fuels, diesel

Result

Rat - Female - Oral
 OECD 414
 100 to 1000 mg/kg
Maternal toxicity: Positive
Fertility effects: Negative
Developmental: Positive

Rat - Male, Female - Oral
 OECD 422
 100 to 750 mg/kg
Maternal toxicity: Negative
Fertility effects: Positive
Developmental: Negative

Conclusion/Summary [Product]

Development: May damage the unborn child.
 Fertility: May damage fertility.
 Effects on or via lactation: Not classified. Based on available data, the classification criteria are not met.

Ingredient name

Fuels, diesel

Conclusion/Summary

Development: May damage the unborn child.
 Fertility: May damage fertility.
 Effects on or via lactation: Not classified. Based on available data, the classification criteria are not met.

Specific target organ toxicity (single exposure)

Not available.

Specific target organ toxicity (repeated exposure)

Product/ingredient name

Fuels, diesel

Result

STOT RE 2, H373 (bone marrow, liver, thymus)

Aspiration hazard

Product/ingredient name

Fuels, diesel

Result

ASPIRATION HAZARD - Category 1

Information on likely routes of exposure

Routes of entry anticipated: Dermal, Inhalation, Eyes.

Potential acute health effects

Inhalation

Harmful if inhaled.

Ingestion

Irritating to mouth, throat and stomach. Aspiration hazard if swallowed -- harmful or fatal if liquid is aspirated into lungs.

Skin contact

Causes skin irritation.

Eye contact

No known significant effects or critical hazards.

Symptoms related to the physical, chemical and toxicological characteristics

Inhalation

Adverse symptoms may include the following:
 nausea or vomiting
 headache
 drowsiness/fatigue
 dizziness/vertigo
 unconsciousness

Ingestion

Adverse symptoms may include the following:
 nausea or vomiting

Skin contact

Adverse symptoms may include the following:
 irritation
 redness

Eye contact

Adverse symptoms may include the following:
 pain or irritation
 watering
 redness

Delayed and immediate effects as well as chronic effects from short and long-term exposure

SECTION 11: Toxicological information

Inhalation	Vapour, mists or fumes may contain polycyclic aromatic hydrocarbons some of which are known to produce skin cancer. May be harmful by inhalation if exposure to vapour, mists or fumes resulting from thermal decomposition products occurs. Vapour, mist or fume may irritate the nose, mouth and respiratory tract.
Ingestion	If swallowed, may irritate the mouth, throat and digestive system. If swallowed, may cause abdominal pain, stomach cramps, nausea, vomiting, diarrhoea, dizziness and drowsiness.
Skin contact	As with all such products containing potentially harmful levels of polycyclic aromatic hydrocarbons, prolonged or repeated skin contact may eventually result in dermatitis or more serious irreversible skin disorders including cancer.
Eye contact	Vapour, mist or fume may cause eye irritation. Exposure to vapour, mist or fume may cause stinging, redness and watering of the eyes.

General	May cause damage to organs through prolonged or repeated exposure. Vapour, mists or fumes may contain polycyclic aromatic hydrocarbons some of which are known to produce skin cancer.
Carcinogenicity	Suspected of causing cancer. Risk of cancer depends on duration and level of exposure.
Mutagenicity	No known significant effects or critical hazards.
Developmental effects	<input checked="" type="checkbox"/> May damage the unborn child.
Fertility effects	<input checked="" type="checkbox"/> May damage fertility.

11.2 Information on other hazards

11.2.1 Endocrine disrupting properties

Conclusion/Summary [Product] This substance/mixture does not contain any components that are considered to have endocrine disrupting properties.

11.2.2 Other information

Not available.

SECTION 12: Ecological information

12.1 Toxicity

Product/ingredient name

uels, diesel

Result

Acute - LL50 - Fresh water

OECD 203
Fish
65 mg/l - Nominal [96 hours]
Effect: Mortality
Based on Diesel fuel

Acute - LL50 - Fresh water

OECD 203
Fish
21 mg/l - Nominal [96 hours]
Effect: Mortality
Based on Diesel fuel

Chronic - NOEL - Fresh water

Modelled data
Fish
0.083 mg/l - Nominal [14 days]
Effect: Mortality
Based on Vacuum gas oil / Hydrocracked gas oil / Distillate Fuel

Acute - EL50 - Fresh water

OECD 202
Daphnia
210 mg/l - Nominal [48 hours]
Effect: Mobility
Based on Diesel fuel

Acute - NOELR - Fresh water

OECD 202
Daphnia
46 mg/l - Nominal [48 hours]
Effect: Mobility
Based on Diesel fuel

Acute - EL50 - Fresh water

OECD 202

Product name Aral Heizöl / Aral HeizölPlus

Product code SGY2152

Page: 13/19

Version 12 **Date of issue** 26 March 2026

Format Germany

Language ENGLISH

Date of previous issue 9 January 2024.

(Germany)

SECTION 12: Ecological information

Daphnia
68 mg/l - Nominal [48 hours]
Effect: Mobility
Based on Diesel fuel

Chronic - NOELR - Fresh water

Modelled data
Daphnia
0.2 mg/l - Nominal [21 days]
Effect: Immobilisation
Based on Vacuum gas oil / Hydrocracked gas oil / Distillate Fuel

Acute - ErL50 - Fresh water

OECD 201
Algae
78 mg/l - Nominal [72 hours]
Effect: (growth rate)
Based on Diesel fuel

Acute - NOELR - Fresh water

OECD 201
Algae
10 mg/l - Nominal [72 hours]
Effect: (growth rate)
Based on Diesel fuel

Acute - EL50 - Fresh water

OECD 201
Algae
22 mg/l - Nominal [72 hours]
Effect: (growth rate)
Based on Diesel fuel

Acute - NOELR - Fresh water

OECD 201
Algae
1 mg/l - Nominal [72 hours]
Effect: (growth rate)
Based on Diesel fuel

EL50 - Fresh water

Modelled data
Micro-organism
>1000 mg/l - Nominal [40 hours]
Effect: growth inhibition
Based on Vacuum gas oil / Hydrocracked gas oil / Distillate Fuel

NOELR - Fresh water

Modelled data
Micro-organism
3.217 mg/l - Nominal [40 hours]
Effect: growth inhibition
Based on Vacuum gas oil / Hydrocracked gas oil / Distillate Fuel

Environmental hazards Toxic to aquatic life with long lasting effects.

12.2 Persistence and degradability

Expected to be biodegradable.

Product/ingredient name

Fuels, diesel

Result

Aerobic - 30 mg/l

OECD 301 F
60% [28 days] - Readily
Based on Diesel fuel

Aerobic - 25 mg/l

OECD 301 F
57.5% [28 days] - Not readily
Based on Diesel fuel

Aerobic - 5 mg/l

Equivalent to EPA OTS 796.3100

Product name Aral Heizöl / Aral HeizölPlus	Product code SGY2152	Page: 14/19
Version 12	Date of issue 26 March 2026	Format Germany
Date of previous issue 9 January 2024.		Language ENGLISH
	(Germany)	

SECTION 12: Ecological information

35% [28 days] - Not readily
Based on Gas Oils (petroleum), solvent refined

12.3 Bioaccumulative potential

This product is not expected to bioaccumulate through food chains in the environment.

12.4 Mobility in soil

Soil/water partition coefficient

Not available.

Results of PMT and vPvM assessment

Product/ingredient name	PMT	P	M	T	vPvM	vP	vM
Fuels, diesel	No	No	No	No	No	No	No

Mobility

Spillages may penetrate the soil causing ground water contamination. This material may accumulate in sediments.

Conclusion/Summary

The product does not meet the criteria to be considered as a PMT or vPvM.

12.5 Results of PBT and vPvB assessment

Regulation (EC) No. 1907/2006 [REACH]

Product/ingredient name	PBT	P	B	T	vPvB	vP	vB
Fuels, diesel	N/A	N/A	N/A	Yes	N/A	N/A	N/A

Regulation (EC) No. 1272/2008 [CLP]

Product/ingredient name	PBT	P	B	T	vPvB	vP	vB
Fuels, diesel	No	No	No	No	No	No	No

Conclusion/Summary

The product does not meet the criteria to be considered as a PBT or vPvB.

Regulation (EC) No. 1272/2008 [CLP]

12.6 Endocrine disrupting properties

Conclusion/Summary [Product]

This substance/mixture does not contain any components that are considered to have endocrine disrupting properties.

Other ecological information

Spills may form a film on water surfaces causing physical damage to organisms. Oxygen transfer could also be impaired.

12.7 Other adverse effects

No known significant effects or critical hazards.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product

Methods of disposal

Where possible, arrange for product to be recycled. Dispose of via an authorised person/ licensed waste disposal contractor in accordance with local regulations.

Hazardous waste

Yes.

European waste catalogue (EWC)

Waste code	Waste designation
13 07 01*	fuel oil and diesel

However, deviation from the intended use and/or the presence of any potential contaminants may require an alternative waste disposal code to be assigned by the end user.

Packaging

Methods of disposal

Where possible, arrange for product to be recycled. Dispose of via an authorised person/ licensed waste disposal contractor in accordance with local regulations.

Special precautions

This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Vapour from product residues may create a highly flammable or explosive atmosphere inside the container. Empty containers represent a fire hazard as they may contain flammable product residues and vapour. Never weld, solder or braze empty containers. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Empty packages may contain some remaining product. Hazard warning labels are a guide to the safe handling of empty packaging and should not be removed.

Product name Aral Heizöl / Aral HeizölPlus

Product code SGY2152

Page: 15/19

Version 12 Date of issue 26 March 2026

Format Germany

Language ENGLISH








Date of previous issue 9 January 2024.

(Germany)

SECTION 13: Disposal considerations

References Commission 2014/955/EU
Directive 2008/98/EC

SECTION 14: Transport information

	ADR/RID	ADN	IMDG	IATA
14.1 UN number or ID number	UN1202	UN1202	UN1202	UN1202
14.2 UN proper shipping name	HEATING OIL, LIGHT	HEATING OIL, LIGHT	HEATING OIL, LIGHT. Marine pollutant	Heating Oil, Light
14.3 Transport hazard class(es)	3  	3  	3  	3 
14.4 Packing group	III	III	III	III
14.5 Environmental hazards	Yes.	Yes.	Yes.	Yes. The environmentally hazardous substance mark is not required.
Additional information	The environmentally hazardous substance mark is not required when transported in sizes of ≤5 L or ≤5 kg. Hazard identification number 30 Tunnel code D/E	The environmentally hazardous substance mark is not required when transported in sizes of ≤5 L or ≤5 kg. Remarks Table: C. Danger:: 3+N2+F	The marine pollutant mark is not required when transported in sizes of ≤5 L or ≤5 kg. Emergency schedules F-E, S-E	The environmentally hazardous substance mark may appear if required by other transportation regulations.

14.6 Special precautions for user Not available.

ADR/RID Classification code: F1

ADN Classification code: F1

14.7 Maritime transport in bulk according to IMO instruments **Proper shipping name** MARPOL Annex 1 rules apply for bulk shipments by sea. Category: gas oils, including ship's bunkers

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

EU Regulation (EC) No. 1907/2006 (REACH)

Annex XIV - List of substances subject to authorisation

Annex XIV

None of the components are listed.

Substances of very high concern

None of the components are listed.

Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles

Product/ingredient name	%	Designation [Usage]
<input checked="" type="checkbox"/> Aral Heizöl / Aral HeizölPlus	95-100	3 3 [Lamp fuel] 3 [Grill lighter fluid] 30
Fuels, diesel	95-100	30
naphthalene	<0.01	50a

Labelling Restricted to professional users.

Other regulations

REACH Status The company, as identified in Section 1, sells this product in the EU in compliance with the current requirements of REACH.

SECTION 15: Regulatory information

United States inventory (TSCA 8b) At least one component is not listed.

Australia inventory (AIIIC) All components are listed or exempted.

Canada inventory At least one component is not listed.

China inventory (IECSC) At least one component is not listed.

Japan inventory (CSCL) At least one component is not listed.

Korea inventory (KECI) At least one component is not listed.

Philippines inventory (PICCS) Not determined.

Taiwan Chemical Substances Inventory (TCSI) Not determined.

Explosive precursors Not applicable.

Ozone depleting substances (EU 2024/590)

Not listed.

Prior Informed Consent (PIC) (649/2012/EU)

Not listed.

Persistent Organic Pollutants

Not listed.

EU - Water framework directive - Priority substances

None of the components are listed.

Seveso Directive

This product is controlled under the Seveso Directive.

Named substances

Name
Petroleum products and alternative fuels (a) gasolines and naphthas, (b) kerosenes (including jet fuels), (c) gas oils (including diesel fuels, home heating oils and gas oil blending streams) (d) heavy fuel oils (e) alternative fuels serving the same purposes and with similar properties as regards flammability and environmental hazards as the products referred to in points (a) to (d)

National regulations

Hazardous incident ordinance

This product is controlled under the Germany Hazardous Incident Ordinance.

Named substances

Name	Reference number
<input checked="" type="checkbox"/> Gas oils (including diesel fuels, home heating oils and gas oil blending streams)	2.3.3

Danger criteria

Category	Reference number
P5c	1.2.5.3
E2	1.3.2

Hazard class for water 2 (classified according AwSV)

Prohibited Chemicals Regulation (ChemVerbotsV) When placed on the market in Germany, this product is subject to the Prohibited Chemicals Regulation (ChemVerbotsV).

Occupational restrictions Observe employment restrictions in the following:
Gesetz zum Schutz der arbeitenden Jugend (Jugendarbeitsschutzgesetz – JArbSchG)
Gesetz zum Schutz von Müttern bei der Arbeit, in der Ausbildung und im Studium (Mutterschutzgesetz – MuSchG)

15.2 Chemical safety assessment

A Chemical Safety Assessment has been carried out for one or more of the substances within this mixture. A Chemical Safety Assessment has not been carried out for the mixture itself.

SECTION 16: Other information

Abbreviations and acronyms

ADN = European Provisions concerning the International Carriage of Dangerous Goods by Inland Waterway
 ADR = The European Agreement concerning the International Carriage of Dangerous Goods by Road
 ATE = Acute Toxicity Estimate
 BCF = Bioconcentration Factor
 CAS = Chemical Abstracts Service
 CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No. 1272/2008]
 CSA = Chemical Safety Assessment
 CSR = Chemical Safety Report
 DMEL = Derived Minimal Effect Level
 DNEL = Derived No Effect Level
 EINECS = European Inventory of Existing Commercial chemical Substances
 ES = Exposure Scenario
 EUH statement = CLP-specific Hazard statement
 EWC = European Waste Catalogue
 GHS = Globally Harmonized System of Classification and Labelling of Chemicals
 IATA = International Air Transport Association
 IBC = Intermediate Bulk Container
 IMDG = International Maritime Dangerous Goods
 LogPow = logarithm of the octanol/water partition coefficient
 MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution)
 OECD = Organisation for Economic Co-operation and Development
 PBT = Persistent, Bioaccumulative and Toxic
 PNEC = Predicted No Effect Concentration
 REACH = Registration, Evaluation, Authorisation and Restriction of Chemicals Regulation [Regulation (EC) No. 1907/2006]
 RID = The Regulations concerning the International Carriage of Dangerous Goods by Rail
 RRN = REACH Registration Number
 SADT = Self-Accelerating Decomposition Temperature
 SVHC = Substances of Very High Concern
 STOT-RE = Specific Target Organ Toxicity - Repeated Exposure
 STOT-SE = Specific Target Organ Toxicity - Single Exposure
 TWA = Time weighted average
 UN = United Nations
 UVCB = Complex hydrocarbon substance
 VOC = Volatile Organic Compound
 vPvB = Very Persistent and Very Bioaccumulative
 Varies = may contain one or more of the following 64741-88-4 / RRN 01-2119488706-23, 64741-89-5 / RRN 01-2119487067-30, 64741-95-3 / RRN 01-2119487081-40, 64741-96-4/ RRN 01-2119483621-38, 64742-01-4 / RRN 01-2119488707-21, 64742-44-5 / RRN 01-2119985177-24, 64742-45-6, 64742-52-5 / RRN 01-2119467170-45, 64742-53-6 / RRN 01-2119480375-34, 64742-54-7 / RRN 01-2119484627-25, 64742-55-8 / RRN 01-2119487077-29, 64742-56-9 / RRN 01-2119480132-48, 64742-57-0 / RRN 01-2119489287-22, 64742-58-1, 64742-62-7 / RRN 01-2119480472-38, 64742-63-8, 64742-65-0 / RRN 01-2119471299-27, 64742-70-7 / RRN 01-2119487080-42, 72623-85-9 / RRN 01-2119555262-43, 72623-86-0 / RRN 01-2119474878-16, 72623-87-1 / RRN 01-2119474889-13

Procedure used to derive the classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Classification	Justification
Flam. Liq. 3, H226 Acute Tox. 4, H332 Skin Irrit. 2, H315 Carc. 2, H351 Repr. 1B, H360FD STOT RE 2, H373 (bone marrow, liver, thymus) Asp. Tox. 1, H304 Aquatic Chronic 2, H411	Expert judgment Expert judgment Calculation method Calculation method Calculation method Calculation method Calculation method Calculation method

Full text of abbreviated H statements	
H226	Flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H332	Harmful if inhaled.
H351	Suspected of causing cancer.
H360FD	May damage fertility. May damage the unborn child.
H373	May cause damage to organs through prolonged or repeated exposure.
H411	Toxic to aquatic life with long lasting effects.

SECTION 16: Other information

Full text of classifications [CLP/GHS]	<input checked="" type="checkbox"/> Acute Tox. 4	ACUTE TOXICITY - Category 4
	Aquatic Chronic 2	LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 2
	Asp. Tox. 1	ASPIRATION HAZARD - Category 1
	Carc. 2	CARCINOGENICITY - Category 2
	Flam. Liq. 3	FLAMMABLE LIQUIDS - Category 3
	Repr. 1B	REPRODUCTIVE TOXICITY - Category 1B
	Skin Irrit. 2	SKIN CORROSION/IRRITATION - Category 2
	STOT RE 2	SPECIFIC TARGET ORGAN TOXICITY - REPEATED EXPOSURE - Category 2

History

Date of issue/ Date of revision	26/03/2026.
Date of previous issue	09/01/2024.
Prepared by	Product Stewardship

Indicates information that has changed from previously issued version.

Notice to reader

All reasonably practicable steps have been taken to ensure this data sheet and the health, safety and environmental information contained in it is accurate as of the date specified below. No warranty or representation, express or implied is made as to the accuracy or completeness of the data and information in this data sheet.

The data and advice given apply when the product is sold for the stated application or applications. You should not use the product other than for the stated application or applications without seeking advice from BP Group.

It is the user's obligation to evaluate and use this product safely and to comply with all applicable laws and regulations. The BP Group shall not be responsible for any damage or injury resulting from use, other than the stated product use of the material, from any failure to adhere to recommendations, or from any hazards inherent in the nature of the material. Purchasers of the product for supply to a third party for use at work, have a duty to take all necessary steps to ensure that any person handling or using the product is provided with the information in this sheet. Employers have a duty to tell employees and others who may be affected of any hazards described in this sheet and of any precautions that should be taken. You can contact the BP Group to ensure that this document is the most current available. Alteration of this document is strictly prohibited.

Product name Aral Heizöl / Aral HeizölPlus	Product code SGY2152	Page: 19/19
Version 12	Date of issue 26 March 2026	Format Germany
Date of previous issue 9 January 2024.	(Germany)	Language ENGLISH